

| | | | | |
|----|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----|---|--|
| | temperature increase on the upper surface of the insole shall not be greater than 22°C | | | |
| 42 | Fire Fighter hand gloves: The gloves shall certify according to EN:659:2004 – Protection gloves for firefighters | No | 2 | |
| 43 | Fire Fighter helmet: High temperature polyamide, shock absorption padding :polyurethane with wool / aramide layer , cradle and chinstrap :aramid straps ,leather , polyamide , polycarbonate. | No | 2 | |
| 44 | Portable Pump | No. | 1 | |

Annex-I Specification of Portable Pump

| Required Specification | | | Offered Specification |
|------------------------|----------------------|------------------------------------------------------------------------------------------|-------------------------------------------|
| General | | | Make: Model No.: Country of Origin: |
| Control | Centralized control | Pressure and vacuum gauges, throttle dial and switches are grouped on the control panel. | |
| Engine: | Type: | 2-stroke, single vertical cylinder, air cooled gasoline engine | |
| | Bore & Stroke: | 66mm x 58mm | |
| | Piston displacement: | Minimum 195 cc | |
| | Authorized output: | Minimum 8.5 kW | |

King
Mechanical Engineer